



BAS716

Small-Signal Fast Switching Diodes

Features

- V_R 75V
- $I_{F(AV)}$ 200mA

Typical Applications

- Fast Switching Speed

Mechanical Data

- **Package:** SOD523
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end
- **Marking:** S1

■ **Maximum Ratings** ($T_a=25$ Unless

^a Peak forward surge current

	I_{FSM}	A	Pulse width=1ms	1
Average forward current	I_{FAV}	mA		200
Power dissipation	P_{tot}	mW		200
Maximum junction temperature	T_j			150
Storage temperature range	T_{stg}			-55 to +150

Electrical Characteristics $T_a=25$ Unless otherwise specified

					Min	Max
Breakdown Voltage	V_R	V	$I_R=100\mu A$		75	
Forward Voltage	V_F	V	$I_F=1mA$			0.9
			$I_F=10mA$			1.0
			$I_F=50mA$			1.1
			$I_F=150mA$			1.25
Reverse Leakage Current	I_R	nA	$V_R=75V$			5



■Ordering Information (Example)



■ Outline Dimensions

■ Soldering Footprint

v
η^s



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.